

CELECCA



METAL ENCLOSURE

WWW.CELECCA.COM



METAL ENCLOSURE

Metal enclosure have industrial, commercial, residential and infrastructure related applications.

Electrical circuit boards are mounted on mounting plates within the enclosure and protected against dust and water by using gasketed doors thereby providing an Ingress Protection of IP66.



METAL ENCLOSURES



■ Application

CT enclosure box is designed to be assembled into the distributing box with various control functions according to the type of components, specifications and quantity.

The structure is so tight that can be very perfect. It's made of cold-rolled steel board or stainless alloy. We can provide a wide range of cabinets for your reference.

■ Construction

- Body and door manufactured in 1.2/1.5mm sheet steel.
- Mounting plate with folded edge in 2.0mm sheet steel
- IP 55/65 protection degree
- Finished with thermosetting epoxy polyester powder coating. Body and door textured finish.
- Mounting plate in smooth finish.

Model	Dimension(mm)		
	A	B	C
CT-2215	200	200	150
CT-2515	250	200	150
CT-2315	300	200	150
CT-2320	300	200	200
CT-3320	300	300	200
CT-3325	300	300	250
CT-3415	400	300	150
CT-3420	400	300	200
CT-3430	400	300	300
CT-4415	400	400	150
CT-4420	400	400	200
CT-4425	400	400	250
CT-4430	400	400	300
CT-3515	500	300	150
CT-3520	500	300	200
CT-3525	500	300	250
CT-3530	500	300	300
CT-4515	500	400	150
CT-4520	500	400	200
CT-4525	500	400	250
CT-4530	500	400	300
CT-5515	500	500	150
CT-5530	500	500	300
CT-4615	600	400	150

Model	Dimension(mm)		
	A	B	C
CT-4620	600	400	200
CT-4630	600	400	300
CT-5620	600	500	200
CT-6615	600	600	150
CT-6620	600	600	200
CT-5720	700	500	200
CT-5725	700	500	250
CT-6720	700	600	200
CT-6820	800	600	200
CT-8820	800	800	200
CT-8830	800	800	300
CT6-1020	1000	600	200
CT6-1025	1000	600	250
CT6-1030	1000	600	300
CT8-1020	1000	800	200
CT10-1025	1000	1000	250
CT10-1030	1000	1000	300
CT6-1220	1000	600	200
CT8-1220	1000	800	200
CT6-1430	1400	600	300
CT8-1430	1400	800	300
CT8-1630	1600	800	300
CT10-1630	1600	1000	300
CT10-1830	1800	1000	300