

CELECCA



CABLE LUGS

WWW.CELECCA.COM





CABLE LUGS

These products are suitable for the connection of copper conductors (section 1.5-1000mm) in power cables with electronic equipment they are made of higher 99.9 percent pure copper tube T2 and coated with tin.
working temperature -55 C-150°C

JOINT FERRULE

These products are applicable for the connection of circular wire, and hemicycle wire with power supply cable in distribution equipment, They are made of higher 99.9 percent pure T2 copper tube, and coated tin.



PIN TYPE LUGS

These products are suitable for the connection of copper conductors (section 1.5-1000mm) in power cables with electronic equipment they are made of higher 99.9 percent pure copper tube T2 and coated with tin.
working temperature -55 C-150°C.

CABLE LUGS

Description SC(JGY) Type	D	d	L
CCL2.5-5	3.8	2.7	19
CCL2.5-6	3.8	2.7	19
CCL4-5	5.0	3.4	21
CCL4-6	5.0	3.4	21
CCL6-5	5.5	3.9	26.5
CCL6-6	5.5	3.9	26.5
CCL6-8	5.5	3.9	26.5
CCL10-6	6.5	4.8	32
CCL10-8	6.5	4.8	32
CCL10-10	6.8	5.2	32
CCL16-6	7.5	5.9	34
CCL16-8	7.5	5.9	34
CCL16-10	7.5	5.9	34
CCL25-8	9.0	7.0	38
CCL25-10	9.0	7.0	38
CCL35-8	10.8	8.6	43
CCL35-10	10.8	8.6	43
CCL35-12	10.8	8.6	43
CCL50-8	12.5	10.1	50
CCL50-10	12.5	10.1	50
CCL50-12	12.5	10.1	50
CCL70-8	14.5	11.9	56
CCL70-10	14.5	11.9	56
CCL70-12	14.5	11.9	56
CCL95-8	16.5	13.5	58
CCL95-10	16.5	13.5	58
CCL95-12	16.5	13.5	58
CCL120-10	19.0	16.0	70
CCL120-12	19.0	16.0	70
CCL150-10	21.0	17.0	75
CCL150-12	21.0	17.0	75
CCL185-10	23.0	18.6	83
CCL185-12	23.0	18.6	83
CCL240-10	26.0	21.4	95
CCL240-12	26.0	21.4	95
CCL300-10	30.0	24.4	110
CCL300-12	30.0	24.4	110

JOINT FERRULE



DESCRIPTION	GTY TYPE	D	d	L
2.5MM		3.7	2.1	20
4MM		4.8	3.2	20
6MM		5.5	3.9	25
10MM		6.5	4.9	30
16MM		7.5	5.9	35
25MM		9	7	40
35MM		10.5	8.3	45
50MM		12.5	10.1	50
70MM		14.5	11.9	55
95MM		17	14	60
120MM		19	16	65
150MM		21	17	70
185MM		24	19.4	75
240MM		26	21.4	80
300MM		30	24.4	85